



gypsemna

METAL PROFILES BY **RONDO**

Maxicote Technical Datasheet

Description

Maxicote is a ready-mixed, quick drying filler with a superior finishing quality specifically for Gypsemna's Gypsum Plasterboards and other inert extenders.

Primary Data

- Copolymer binders
- Precisely graded marble fillers
- Dilution with water, if required
- Average consumption of 1.75 kg / m² per mm thickness
- 1.75 kg per litre density
- Negligible shrinkage
- Non-toxic
- 28 kg bucket packaging
- 12 months storage, (protected conditions) in original unopened containers:

Technical Data

Standard Compliance

ASTM C 475

Application

“Maxicote” is designed to provide thin skim coats, to embed and to finish joint tapes, corner tapes as well as corner beads and other reinforcement- and finishing profiles. Maxicote is in particular recommended to be used with Gypsemna gypsum plasterboards and systems.



gypsemna

METAL PROFILES BY **RONDO**

Handycoat Technical Datasheet

Description

Handycoat is a ready to use filler for use on all common building surfaces, including timber. It gives a high quality, even surface for painting. Handycoat is specifically manufactured for the painter to repair and touch up exterior and interior surfaces, both new and old, prior to painting. It is designed for filling joints, hairline cracks etc. by hand application. Unlike conventional fillers, Handycoat has elastic properties, does not flake off, is permanent and retains its adhesion.

Primary Data

- Styrene Acrylate
- Fine precisely graded fillers
- Dilution with water, if required
- 1.75 kg per litre density
- Negligible shrinkage
- Non-toxic
- 28 kg bucket packaging
- 12 months storage, (protected conditions) in original unopened containers:

Technical Data

Application

Handycoat Exterior is suitable for exterior as well as interior surfaces. When dry, Handycoat Exterior is weather resistant and bonds extremely well to cementitious materials, gypsum, gypsum boards, sprayplaster, wood, galvanised and primed antirust steel surfaces etc. As a thin coat filler for patching hairline cracks in walls, ceilings, soffits, repair to damaged plasterwork, paintwork, filling holes and defects in woodwork, making good to exposed concrete, filling of dents in galvanised and anti-rust primed metal.