



GYPSEMNA HDU TRACK

METAL PROFILES




DESCRIPTION

Gypsemna Head Deflection U Track provides a friction-fit for the studs, holding them in position until the lining board is installed and assisting in board alignment. Components for drywall studs and tracks are cold roll-formed from hot-dipped galvanized steel (corrosion resistant) and are available in a variety of sizes and thicknesses.

BASIC USES

Gypsemna Head Deflection U Track is the horizontal top member of drywall structure into which the corresponding Gypsemna's CH and E Stud is fitted. It allows a vertical movement from the ceiling or roof which prevents loads from being transferred to the studs. It is a strong, non-load bearing component for exterior and interior drywall partitions, ceilings and liners.



ADVANTAGES

- Provides a smooth, monolithic wall finish.
- Fire-resistant performance.
- Flexible configuration options.
- Dimensionally stable.
- Impervious to rot, fungal growth and insect attack.
- Corrosion-resistant.
- Will not warp, twist, or bow.
- Easy to cut and install; minimal tools required.
- Non-combustible.

TECHNICAL DATA

PHYSICAL PROPERTIES

Coating	Z120, Z180 and Z275 Zinc coating
Standard compliance	ASTM C645 / ASTM A653 / ASTM A645/ ASTM A370
Material	Cold roll-formed from hot-dipped galvanized steel
Grade	G300
Minimum yield strength	300 MPa
Minimum tensile strength	340 MPa
Available thicknesses (mm)	0.5, 0.55, 0.6, 0.7, 0.8, 0.9, 1.0, 1.1, 1.2, 1.3 and 1.5
Flange (mm)	50
Width (mm)	52, 66, 72, 78, 94, 102, 127 and 152
Length (mm)	3000