



GYPSEMNA

**Joining Compound
Exterior**

**Finishing
Components**

JOINING COMPOUND



■ DESCRIPTION

Gypsemna JCE is a ready-to-use filler suitable for application on all common building surfaces, including timber. It provides a smooth, high-quality surface ideal for painting. It is used to repair and touch up both new and existing interior and exterior surfaces prior to painting. It is designed for filling joints and hairline cracks by hand application. Unlike conventional fillers, Joining Compound Exterior has elastic properties, does not flake remains permanent and maintains strong adhesion.

■ APPLICATION

Joining Compound Exterior is suitable for both exterior and interior surfaces. When dry, it is weather-resistant and adheres strongly to cementitious materials, gypsum, gypsum boards, spray plaster, wood, and galvanized or primed anti-rust steel surfaces. It can be used as a thin-coat filler for patching hairline cracks in walls, ceilings, and soffits; repairing damaged plasterwork and paintwork; filling holes and defects in woodwork; leveling exposed concrete; and filling dents in galvanized or anti-rust primed metal surfaces.

■ ADVANTAGES

- Styrene Acrylate
- Fine, precisely graded
- Dilution with water, if required
- 1.75kg per litre density
- Negligible shrinkage
- Non-toxic
- Packaging: 25kg bucket
- Shelf Life: 12 months when stored in original sealed containers under protected conditions

■ STANDARDS

- Compiles with ASTM C475/C475M.
- Suitable for achieving finishing levels in accordance with ASTM C840.