



## GYPSEMNA WEDGE ANCHOR

### FIXING COMPONENTS



### DESCRIPTION

Galvanized steel 6 mm diameter anchor made for multiple use for non-structural cracked and uncracked concrete. The head of the ceiling anchor rests wide, covers neatly and has an expansible split part on the other side. Suitable for fire rated systems. It is commonly used for fixing hangers, brackets, and various drywall profiles to concrete slabs, particularly in applications requiring high load capacity, safety, and rapid installation.

### BASIC USES

Wedge Anchor is suitable for use in all drywall systems, including suspended ceilings, substructures, metal profiles, ventilation systems, and wire hangers.

### ADVANTAGES


- High mechanical strength.
- Excellent dimensional stability.
- Compatible with all major façade systems.
- Simple installation.
- Reliable setting with easy visual inspection.
- Suitable for fixing in cracked concrete (for redundant fastening only).

### TECHNICAL DATA


#### PHYSICAL PROPERTIES

Standard Compliance	BS 212.15 / ASTM E488
Material	Cold-formed steel
Coating	Zinc coating
Size	6 x 40mm and 6 x 70mm


### Installation




Drill hole with drill bit.



Blow out dust and fragments.



Install anchor with suspended item.



Hammer in anchor.